



2013 FOURTRAX RANCHER SPECIFICATIONS

ENGINE	
Engine Type	420cc liquid-cooled fuel-injected OHV wet-sump longitudinally mounted single-cylinder four-stroke
Bore and Stroke	86.5mm x 71.5mm
Induction	Keihin® 34mm throttle-body fuel-injection system
Ignition	Electric with optional auxiliary recoil
DRIVE TRAIN	
Clutch	Automatic
Transmission	Five-speed with Reverse
Driveline	Direct rear driveshaft
DRIVE TRAIN CHASSIS / SUSPENSION / BRAKES	
Front Suspension	Independent double-wishbone; 6.3 inches travel
Rear Suspension	Swingarm with single shock; 6.3 inches travel
Front Brake	Dual hydraulic disc
Rear Brake	Sealed mechanical drum
Front Tire	24 x 8-12
Rear Tire	24 x 10-11
DIMENSIONS	
Length	80.9 inches
Width	46.1 inches
Height	45.1 inches
Wheelbase	49.2 inches
Seat Height	32.4 inches
Ground Clearance	6.5 inches
Curb Weight	547 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.5 gallons, including 1.0-gallon reserve
Turning Radius	8.9 feet
OTHER	
Model ID	TRX420TM
Emissions	Meets current California Air Resources Board (CARB) and EPA off-road emissions standards
Colors	Red, Olive
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.
FACTORY WARRANTY INFORMATION	
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan