



2013 FOURTRAX RANCHER AT SPECIFICATIONS

ENGINE

Engine Type	420cc liquid-cooled fuel-injected OHV wet-sump longitudinally mounted single-cylinder four-stroke
Bore and Stroke	86.5mm x 71.5mm
Induction	Programmed Fuel Injection (PGM-FI), 34mm throttle bodies
Ignition	Full-transistorized type with electronic advance
Starter	Electric with optional auxiliary recoil

DRIVE TRAIN

Clutch	Automatic
Transmission	Automatic
Driveline	Direct front and rear driveshafts

DRIVE TRAIN CHASSIS / SUSPENSION / BRAKES

Front Suspension	Independent double-wishbone; 6.3 inches travel
Rear Suspension	Independent double-wishbone; 6.3 inches travel
Front Brake	Dual hydraulic disc
Rear Brake	Single hydraulic disc
Front Tire	24 x 8-12
Rear Tire	24 x 10-11

DIMENSIONS

Length	80.9 inches
Width	46.1 inches
Height	45.8 inches
Wheelbase	49.4 inches
Seat Height	32.9 inches
Ground Clearance	9.1 inches
Curb Weight	624 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.6 gallons, including 1.0-gallon reserve
Turning Radius	10.5 feet

OTHER

Model ID	TRX420FA
Emissions	Meets current California Air Resources Board (CARB) and EPA off-road emissions standards
Colors	Red, Olive, Natural Gear™ Camo
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan
----------	---