



2013 TRX400X SPECIFICATIONS

ENGINE	
Engine Type	397cc RFVCTM air-cooled dry-sump single-cylinder four-stroke
Bore and Stroke	85mm x 70mm
Induction	Programmed Fuel Injection (PGM-FI), 50mm throttle body)
Ignition	CD with electronic advance
Starter	Electric
DRIVE TRAIN	
Clutch	Manual
Transmission	Five-speed with Reverse
Driveline	O-ring-sealed chain
CHASSIS / SUSPENSION / BRAKES	
Front Suspension	Independent double-wishbone with Showa® shocks, five-position spring-preload adjustability; 8.2 inches travel
Rear Suspension	Pro-Link® fully adjustable single Showa shock; 9.1 inches travel
Front Brake	Dual hydraulic 174mm discs
Rear Brake	Single 220mm disc
Front Tire	22 x 7-10 knobby radial
Rear Tire	20 x 10-9 knobby
DIMENSIONS	
Length	71.7 inches
Width	45.5 inches
Height	44.0 inches
Wheelbase	47.9 inches
Seat Height	32.8 inches
Ground Clearance	4.1 inches
Curb Weight	408 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	2.6 gallons, including 0.4 gallon reserve
Turning Radius	10.5 feet
OTHER	
Model ID	TRX400X
Emissions	Meets current California Air Resources Board (CARB) off-road emissions standards.
Available Color	Red
Note	For highly experienced riders only; no operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.