




2014 Honda Pioneer Models compared with 2013 Big Red	 2014 Pioneer 700 <ul style="list-style-type: none"> • 675cc liquid-cooled OHV single-cylinder four-stroke • Honda Automatic Transmission Starting at \$9,999	 2013 Big Red <ul style="list-style-type: none"> • 675cc liquid-cooled OHV single-cylinder four-stroke • Honda Automatic Transmission Starting at \$11,699	 2014 Pioneer 700-4 <ul style="list-style-type: none"> • 675cc liquid-cooled OHV single-cylinder four-stroke • 2-3-4 Seating Configuration • Honda Automatic Transmission Starting at \$11,699
- ENGINE			
Engine Type	675cc liquid-cooled OHV single-cylinder four-stroke	675cc liquid-cooled OHV single-cylinder four-stroke	675cc liquid-cooled OHV single-cylinder four-stroke
Bore And Stroke	102.0mm x 82.6mm	102mm x 82.6mm	102.0mm x 82.6mm
Compression Ratio	9.2:1	9.2:1	9.2:1
Induction	Fuel Injection (POM-FI), 40mm throttle body	Electronic fuel injection (POM-FI), 40mm throttle body	Fuel Injection (POM-FI), 40mm throttle body
Ignition	Full-transistorized with electronic advance	Full-transistorized type with electronic advance	Full-transistorized with electronic advance
- DRIVE TRAIN			
Clutch	Automatic	Automatic	Automatic
Transmission	Automotive-style with hydraulic torque converter, three forward gears and Reverse. Three drive modes include 2WD, 4WD and 4WD with differential lock	Automotive-style with hydraulic torque converter, three forward gears and Reverse, three drive modes: 2WD, 4WD, and 4WD with all-wheel differential lock	Automotive-style with hydraulic torque converter, three forward gears and Reverse. Three drive modes include 2WD, 4WD and 4WD with differential lock
Driveline	Direct front and rear driveshafts	Direct front and rear driveshafts	Direct front and rear driveshafts
- CHASSIS / SUSPENSION / BRAKES			
Front Suspension	Independent double-wishbone, 7.9 inches travel	Independent double-wishbone, 5.9-inch travel	Independent double-wishbone, 7.9 inches travel
Rear Suspension	Independent double-wishbone, 9.1 inches travel	Independent double-wishbone, 7.1-inch travel with adjustable preload	Independent double-wishbone, 9.1 inches travel
Front Brake	200mm hydraulic disc	200mm hydraulic disc with 51.1mm caliper	200mm hydraulic disc
Rear Brake	170mm hydraulic disc	200mm hydraulic disc with 30.3mm caliper	170mm hydraulic disc
Front Tires	25 x 8-12	Maxxis Big Horn 25 x 10-12 bias	25 x 8-12
Rear Tires	25 x 10-12	Maxxis Big Horn 25 x 10-12 bias	25 x 10-12
- DIMENSIONS			
Length	114.8 inches	114.7 inches	114.8 inches
Width	60.0 inches	64.0 inches	60.0 inches
Height	77.6 inches	76.9 inches	78.3 inches
Wheelbase	76.8 inches	75.7 inches	76.8 inches
Bed Capacity	1000 pounds	1,000 lbs.	1000 pounds
Towing Capacity	1500 pounds	1,500 lbs.	1500 pounds
Ground Clearance	10.3 inches	10.3 inches	10.3 inches
Turning Radius	14.8 feet	13.8 feet	14.8 feet
Curb Weight	1261 pounds - Includes all standard equipment, required fluids and full tank of fuel/ready to ride.	1,433 lbs. (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)	1396 pounds
Fuel Capacity	8.2 gallons, including 1.2-gallon reserve	7.9 Gallons, including 1.5-gallon reserve	8.2 gallons, including 1.2-gallon reserve
- OTHER			
Note	675cc liquid-cooled OHV single-cylinder four-stroke	Recommended for Drivers 16 years of age and older. Honda recommends that all MUV drivers read the owner's manual thoroughly. Occupant protection structure now meets the requirements of OSHA 1928.53 Rollover Protection Standard.	675cc liquid-cooled OHV single-cylinder four-stroke
Available Colors	Red, Olive, Honda Phantom Camo™	Red, Olive, Natural Gear™ Camo	Red, Olive, Honda Phantom Camo™
Model Id	SXS700M2	MUV700	SXS700M4
- FACTORY WARRANTY INFORMATION			
Duration	One Year	One Year	One Year
Description	Transferable limited warranty, extended coverage available with a Honda Protection Plan	Transferable limited warranty, extended coverage available with a Honda Protection Plan	Transferable limited warranty, extended coverage available with a Honda Protection Plan