

# 2019 MAVERICK™ SPORT

## HIGHLIGHTS

### DARING

- Sturdy engine and transmission
- Enhanced comfort and meaningful functionalities
- Can-Am design

### PRECISE

- Easy handling and capabilities
- Suspensions designed for performance
- Ultra-resistant chassis

### CONFIDENT

- Perfectly tuned
- Enhanced protection
- More adventure and less maintenance

### SPECIFIC TO PACKAGE

- Visco-Lok† auto-locking front differential
- Ergoprint seats



White / 1000

## ENGINE

### 1000

|                      |  |
|----------------------|--|
| Type                 | 75 hp, Rotax® 976 cc, V-twin, liquid cooled  |
| Fuel Delivery System | Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)  |
| Transmission         | Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P |
| Drive Train          | Selectable 2WD / 4WD with Visco-Lok† auto-locking front differential   |
| Driving Assistance   | Electronic Hill Descent Control  |
| Power Steering       | N/A  |

## SUSPENSIONS

|                  |  |
|------------------|--|
| Front Suspension | Double A-arm with sway bar / 11.5 in. (29.2 cm) travel |
| Front Shocks     | FOX† 2.0 PODIUM  |
| Rear Suspension  | TTA with sway bar / 12 in. (30.5 cm) travel            |
| Rear Shocks      | FOX† 2.0 PODIUM  |

## BRAKES

|       |  |
|-------|--|
| Front | Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear  | Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers |

## TIRES / WHEELS

|             |   |
|-------------|---|
| Front Tires | Maxxis Bighorn 2.0<br>27 x 9 x 12 in.<br>(68.6 x 22.9 x 30.5 cm)  |
| Rear Tires  | Maxxis Bighorn 2.0<br>27 x 11 x 12 in.<br>(68.6 x 27.9 x 30.5 cm) |
| Wheels      | 12-in. (30.5 cm) cast-aluminum                                    |

## DIMENSIONS / CAPACITIES

|                    |   |
|--------------------|---|
| L x W x H          | 119 x 60 x 71.1 in.<br>(302.2 x 152.4 x 180.6 cm)   |
| Wheelbase          | 90.6 in. (230.1 cm)   |
| Ground Clearance   | 12 in. (30.5 cm)  |
| Dry Weight         | 1,377 lb (625.9 kg)   |
| Cage               | ROPS-approved profiled cage.<br>Certified ISO 3471.   |
| Cargo Box Capacity | 300 lb (136 kg)   |
| Storage Capacity   | Total: 5.3 gal (20.2 L)<br>Glove Box: 4.1 gal (15.6 L)<br>Driver storage: 0.4 gal (1.5 L)<br>Center console and Cup holders:<br>0.8 gal (3.1 L) |
| Towing capacity    | 1,500 lb (680 kg)   |
| Fuel Capacity      | 10 gal (38 L)   |

## FEATURES

|                 |   |                |   |
|-----------------|---|----------------|---|
| Gauge           | Multifunction digital:<br>Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, seat belt, diagnostics, clock | Winch          | N/A   |
| Instrumentation | Lighter type DC outlet in console (20-A)  | Steering Wheel | Adjustable tilt steering  |
| Magneto         | 650-W   | Protection     | Integrated front steel bumper, injected full skid plates, premium half doors, mudguards |
| Lighting        | Two 55 W reflectors and LED tail lights   | Hitch Type     | 2-in hitch receiver   |

## WARRANTY

|          |                                   |
|----------|-----------------------------------|
| Factory  | 6-months limited warranty         |
| Extended | Up to 30 months B.E.S.T. coverage |

**BEST PROTECTION** ©2018 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. †All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

**can-am**

Can-AmOffroad.com

