

COMPARE MODEL SPECIFICATIONS



2019 Wolverine X2



2019 Wolverine X2 R-S ✖



2019 Wolverine X2 R-S ✖

MSRP*	\$12,699 - Graphite - Available from June 2018	\$14,949 - Realtree Edge w/Suntop & Aluminum Wheels - Available from July 2018 \$14,499 - Ridge Red w/Suntop & Aluminum Wheels - Available from June 2018 \$14,499 - Alpine White w/Suntop & Aluminum Wheels - Available from June 2018	\$15,299 - Tactical Black w/Suntop & Aluminum Wheels - Available from July 2018 \$15,299 - Backcountry Blue w/Suntop & Aluminum Wheels - Available from July 2018
--------------	--	---	--

Engine

Engine Type	847cc parallel-twin, liquid-cooled, DOHC; 8 valves	847cc parallel-twin, liquid-cooled, DOHC; 8 valves	847cc parallel-twin, liquid-cooled, DOHC; 8 valves
Bore x Stroke	82.0mm x 80.2mm	82.0mm x 80.2mm	82.0mm x 80.2mm
Compression Ratio	10.5:1	10.5:1	10.5:1
Fuel Delivery	Mikuni® fuel injection with YCC-T, dual 36mm throttle bodies	Mikuni® fuel injection with YCC-T, dual 36mm throttle bodies	Mikuni® fuel injection with YCC-T, dual 36mm throttle bodies
Transmission	Ultramatic V-belt with all-wheel engine braking; L, H, N, R	Ultramatic V-belt with all-wheel engine braking; L, H, N, R	Ultramatic V-belt with all-wheel engine braking; L, H, N, R
Final Drive	On-Command 3-way locking differential; 2WD, 4WD, full diff-lock 4WD	On-Command 3-way locking differential; 2WD, 4WD, full diff-lock 4WD	On-Command 3-way locking differential; 2WD, 4WD, full diff-lock 4WD

Chassis

Suspension / Front	Independent double wishbone w/anti-sway bar, preload adjustable; 8.7-in travel	Independent double wishbone w/anti-sway bar, fully adjustable KYB® piggyback shocks; 8.7-in travel	Independent double wishbone w/anti-sway bar, fully adjustable KYB® piggyback shocks; 8.7-in travel
Suspension / Rear	Independent double wishbone w/anti-sway bar, preload adjustable; 8.9-in travel	Independent double wishbone w/anti-sway bar, fully adjustable KYB® piggyback shocks; 8.9-in travel	Independent double wishbone w/anti-sway bar, fully adjustable KYB® piggyback shocks; 8.9-in travel
Brakes / Front	Dual hydraulic disc	Dual hydraulic disc	Dual hydraulic disc
Brakes / Rear	Dual hydraulic disc, shaft-mounted parking brake	Dual hydraulic disc, shaft-mounted parking brake	Dual hydraulic disc, shaft-mounted parking brake
Tires / Front	AT26 x 8-12 Maxxis® MU75	AT26 x 8-12 Maxxis® MU75	AT26 x 8-12 Maxxis® MU75
Tires / Rear	AT26 x 10-12 Maxxis® MU76	AT26 x 10-12 Maxxis® MU76	AT26 x 10-12 Maxxis® MU76

Dimensions

L x W x H	115.0 in x 59.1 in x 74.8 in	115.0 in x 59.1 in x 74.8 in	115.0 in x 59.1 in x 74.8 in
Wheelbase	82.7 in	82.7 in	82.7 in
Turning Radius	177.0 in	177.0 in	177.0 in
Maximum Ground Clearance	11.0 in	11.0 in	11.0 in
Fuel Capacity	9.2 gal	9.2 gal	9.2 gal
Wet Weight	1541 lb	1586 lb	1586 lb
Bed Capacity	600 lb	600 lb	600 lb
Towing Capacity	2000 lb	2000 lb	2000 lb
Other			
Warranty	6 Month (Limited Factory Warranty)	6 Month (Limited Factory Warranty)	6 Month (Limited Factory Warranty)