

# 2019 OUTLANDER™ MAX 6x6 DPS™ 450

## HIGHLIGHTS

- Rotax® single cylinder engine
- Continuously Variable Transmission (CVT) with extra low L-gear
- 26-in. Carlisle† ACT tires
- 12-in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS)
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Double A-arm front suspension
- Relocated air intakes
- RF Digitally Encoded Security System (D.E.S.S.)
- 2.9-gal (10.9 L) water-resistant rear compartment
- Cargo extenders
- 350-lb (159 kg) capacity rear bed with cargo extenders
- Dynamic passenger comfort ergonomics
- Quick release sway bar



Green / 450

ENGINE	450
Type	38 hp, Rotax 427 cc single cylinder, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok QE† auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22 cm) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	Carlisle ACT radial 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT radial 26 x 10 x 12 in (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES	
L x W x H	118 x 46 x 57 in (300 x 117 x 145 cm)
Wheelbase	90 in. (228.5cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	33.8 in. (85.8 cm)
Dry Weight	1000 lb (454 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 350 lb (159 kg)
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES			
Gauge	Multifunction digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	70 W from dual 35-W front light / brake light
Protection	Central skid plate	Seat	Convertible Rack System (CRS)
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage

**BEST PROTECTION** ©2018 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GMI Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

**can-am.**

Can-AmOffroad.com

