

| | |
|------------------|--|
| MODEL | 2009 Outlander™ 500 EFI |
| M.S.R.P. * | \$7,499.00 |
| LENGTH | 86 in. (2,184 mm) |
| HEIGHT | 45 in. (1,143 mm) |
| WIDTH | 46 in. (1,168 mm) |
| WEIGHT | 645 lbs. (293 kg) |
| GROUND CLEARANCE | 11 in. (279 mm) |
| WHEELBASE | 51 in. (1,295 mm) |
| SEAT HEIGHT | 34.5 in. (877 mm) |
| ENGINE | V-twin, SOHC, 8-valve (4-valve / cylinder) |
| DISPLACEMENT | 499.6 cc |
| BORE X STROKE | 82 x 47 mm |
| CARBURETION | EFI, 46 mm throttle body, 2 Siemens VDO injectors |
| FUEL CAPACITY | 5.3 gal. (20 l) |
| STARTING | Electric |
| COOLING | Liquid |
| TRANSMISSION | CVT, sub-transmission with high, low, park, neutral & reverse, standard engine braking |
| DRIVE SYSTEM | 4x4 |
| BRAKES | Front: 2 inboard hydraulic discs Rear: 1 inboard hydraulic disc |
| TIRES | Front: 25 x 8 x 12 in. (635 x 203 x 305 mm) Rear: 25 x 10 x 12 in. (635 x 254 x 305 mm) |
| SUSPENSION | Front: McPherson; 7 in. (178 mm) travel Rear: TTI independent; 9 in. (229 mm) travel |
| LOAD CAPACITY | Front Rack: 100 lbs. (45 kg) Rear Rack: 200 lbs. (90 kg) |
| TOWING CAPACITY | 1,300 lbs. (590 kg) |