



2013 FOURTRAX RINCON SPECIFICATIONS

ENGINE

Engine Type	675cc liquid-cooled OHV semi-dry-sump longitudinally mounted single-cylinder four-stroke
Bore and Stroke	102mm x 82.6mm
Induction	Electronic fuel injection (PGM-FI), 40mm throttle bodies
Ignition	Full-transistorized type with electronic advance
Starter	Electric with auxiliary recoil

DRIVE TRAIN

Clutch	Automatic
Transmission	Automatic with hydraulic torque converter, three forward gears, Reverse, and electronic controls
Driveline	Direct front and rear driveshafts with TraxLok® and torque-sensitive front differential

DRIVE TRAIN CHASSIS / SUSPENSION / BRAKES

Front Suspension	Independent double-wishbone; 6.9 inches travel
Rear Suspension	Swingarm with single shock; 8.0 inches travel
Front Brake	Dual hydraulic 180mm disc
Rear Brake	Single hydraulic disc
Front Tire	25 x 8-12 radial
Rear Tire	25 x 10-12 radial

DIMENSIONS

Length	83.2 inches
Width	46.8 inches
Height	47.5 inches
Wheelbase	50.8 inches
Seat Height	34.5 inches
Ground Clearance	10.0 inches
Curb Weight	648 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	4.3 gallons, including 1.2-gallon reserve
Turning Radius	10.8 feet

OTHER

Model ID	TRX680FA
Emissions	Meets current California Air Resources Board (CARB) and EPA off-road emissions standards
Colors	Red, Olive, NaturalGear™ Camouflage
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan
----------	---