



2009 TRX700XX SPECIFICATIONS

ENGINE

Engine Type	686cc liquid-cooled SOHC dry-sump single-cylinder four-stroke
Bore and Stroke	102mm x 84mm
Induction	Keihin® PGM-FI with a 44mm throttle-body fuel injection system
Ignition	Full-transistorized type with electronic advance
Starter	Electric

DRIVE TRAIN

Clutch	Manual
Transmission	Five-speed with Reverse
Driveline	O-ring-sealed #520 chain

CHASSIS / SUSPENSION / BRAKES

Front Suspension	Independent double-wishbone with dual single-rate springs; 10.5 inches travel
Rear Suspension	Independent double-wishbone with piggy-back reservoir shocks; 9.3 inches travel
Front Brake	Dual hydraulic 174mm discs
Rear Brake	Single hydraulic 200mm discs
Front Tire	21 x 7R-10
Rear Tire	22 x 9R-11

DIMENSIONS

Length	73.9 inches
Width	46.3 inches
Height	45.4 inches
Wheelbase	50 inches
Seat Height	33 inches
Ground Clearance	10.5 inches
Curb Weight	505 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3 gallons

OTHER

Model ID	TRX700XX
Emissions	Meets current California Air Resources Board (CARB) off-road emissions standards.
Available Colors	Metallic Black with graphics, Metallic Black/Silver, Metallic Black/Red
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.
----------	--