



2013 Grizzly 550 FI Auto. 4x4    2013 Grizzly 550 FI Auto. 4x4 EPS

MSRP*	\$7,999 (Hunter Green) Available from June 2012 \$7,999 (Steel Blue) Available from June 2012 \$8,449 (Realtree AP HD Camo) Available from June 2012	\$8,699 (Hunter Green) Available from June 2012 \$8,949 (Steel Blue w/Aluminum Wheels) Available from June 2012 \$9,149 (Realtree AP HD Camo) Available from June 2012
-------	--	--

Engine		
Bore x Stroke	92.0 x 84.0mm	92.0 x 84.0mm
Compression Ratio	9.3:1	9.3:1
Drive Train	Yamaha On-Command® pushbutton; 3-way locking differential; 2WD, 4WD, locked 4WD; shaft drive	Yamaha On-Command® pushbutton; 3-way locking differential; 2WD, 4WD, locked 4WD; shaft drive
Fuel Delivery	Yamaha Fuel Injection (YFI), 40mm	Yamaha Fuel Injection (YFI), 40mm
Ignition	TCI, 32-bit ECU	TCI, 32-bit ECU
Starting System	Electric	Electric
Transmission	Yamaha Ultramatic® V-belt with all-wheel engine braking/H, L, N, R, P	Yamaha Ultramatic® V-belt with all-wheel engine braking/H, L, N, R, P
Type	558cc, 4-stroke, liquid-cooled single; SOHC, 4 valves	558cc, 4-stroke, liquid-cooled single; SOHC, 4 valves

Chassis		
Brakes / Front	Dual hydraulic disc	Dual hydraulic disc
Brakes / Rear	Dual hydraulic disc	Dual hydraulic disc
Suspension / Front	Independent double wishbone; 5-way preload adjustment, 7.1-in travel	Independent double wishbone; 5-way preload adjustment, 7.1-in travel
Suspension / Rear	Independent double wishbone; 5-way preload adjustment, 9.5-in travel	Independent double wishbone; 5-way preload adjustment, 9.5-in travel
Tires / Front	AT25 x 8-12	AT25 x 8-12
Tires / Rear	AT25 x 10-12	AT25 x 10-12

Dimensions		
Fuel Capacity	5.3 gal	5.3 gal
Ground Clearance	10.8 in	10.8 in
L x W x H	81.3 x 46.5 x 48.8 in	81.3 x 46.5 x 48.8 in
Rack Capacity	99 lb Fr./187 lb Rr.	99 lb Fr./187 lb Rr.
Seat Height	35.6 in	35.6 in
Towing Capacity	1322 lb	1322 lb
Turning Radius	126 in	126 in
Wet Weight	648 lb	648 lb
Wheelbase	49.2 in	49.2 in

Other			
Instrumentation	Digital LCD multifunction display; speedometer, odometer, dual tripmeter, hour meter, clock, fuel gauge and gear position	Digital LCD multifunction display; speedometer, odometer, dual tripmeter, hour meter, clock, fuel gauge and gear position	
Lighting	Dual 35W Halogen multireflector headlights & 21W/5W brakelight	Dual 35W Halogen multireflector headlights & 21W/5W brakelight	
Warranty	6 Month (Limited Factory Warranty)	6 Month (Limited Factory Warranty)	

ATVs with engines 70 to 90cc are recommended for use only by riders 12 years and older and always with adult supervision. ATVs with engines 90cc or greater are recommended for use only by riders ages 16 years and older. • Yamaha recommends that all ATV riders take an approved training course. For safety and training information, see your dealer or call the ATV Safety Institute at 1-800-887-2887. • ATVs can be hazardous to operate. For your safety, always avoid paved surfaces. Never ride on public roads. Always wear a helmet, eye protection and protective clothing. Never carry passengers. Never engage in stunt riding. Riding and alcohol/drugs don't mix. Avoid excessive speed. And be particularly careful on difficult terrain. There are few joys in life equal to the free-spirited thrill and experience of ATV riding. And that's why it's important for all of us to do our part as responsible riders. By following logical, common-sense rules, we can maintain season after season of unparalleled enjoyment of our sport. • Please remember to "tread lightly." Always ride in a responsible manner, respecting the environment as well as all state and local laws. The riders in this brochure are professionals; don't attempt to emulate them. Prices and specifications subject to change without notice. Please read your Owner's Manual and all labels before operation. All ATVs come with a six-month Limited Factory Warranty. See your dealer for details.

©2012 Yamaha Motor Corporation, U.S.A.