



2012 Rhino 700 FI Auto. 4x4 Sport Edition



2009 Rhino 700 FI Auto. 4x4

2009 Rhino 450 Auto. 4x4

MSRP*	\$13,399 (Metallic Sandstone) Available from July, 2011	\$10,999 (Hunter Green) \$10,999 (Steel Blue) \$11,549 (Realtree® AP HD® Camouflage)	\$8,799 (Red) \$8,799 (Hunter Green) \$9,349 (Realtree® AP HD® Camouflage)
-------	---	--	--

<b>Engine</b>			
Bore x Stroke	102.0 x 84.0mm	102.0 x 84.0mm	84.5mm x 75mm
Compression Ratio	9.2:1	9.2:1	10.0:1
Drive Train	Yamaha On-Command® pushbutton; 3-way locking differential; 2WD,4WD, locked 4WD; shaft drive	Yamaha On-Command® pushbutton; 3-way locking differential; 2WD,4WD, locked 4WD; shaft drive	Yamaha On-Command® pushbutton; 3-way locking differential; 2WD,4WD, locked 4WD; shaft drive
Engine Braking	Spec Not Available	All wheel	Spec Not Available
Fuel Delivery	Yamaha Fuel Injection (YFI) , 41mm	Yamaha Fuel Injection (YFI) , 41mm	Mikuni 33mm BSR
Ignition	32 Bit ECU	32 Bit ECU	DC – CDI
Starting System	Electric	Electric	Electric
Transmission	Yamaha Ultramatic® V-belt with all-wheel engine braking/H, L, N, R	Yamaha Ultramatic® V-belt with all-wheel engine braking/H, L, N, R	Yamaha Ultramatic® V-belt with all-wheel engine braking/H, L, N, R
Type	686cc liquid-cooled w/fan, 4-stroke; SOHC, 4 valves	686cc liquid-cooled w/fan, 4-stroke; SOHC, 4 valves	421cc liquid-cooled w/fan, 4-stroke; SOHC, 4 valves

<b>Chassis</b>			
Brakes / Front	Dual hydraulic disc, twin piston	Dual hydraulic disc, twin piston	Dual hydraulic disc, twin piston
Brakes / Rear	Dual hydraulic disc	Dual hydraulic disc	Hydraulic disc, self-adjusting, shaft mounted
Suspension / Front	Independent double wishbone; 5-way preload adjustment, 7.3-in travel	Independent double wishbone; 5-way preload adjustment, 7.3-in travel	Independent double wishbone; 5-way preload adjustment, 7.3-in travel
Suspension / Rear	Independent double wishbone; 5-way preload adjustment, 7.3-in travel	Independent double wishbone; 5-way preload adjustment, 7.3-in travel	Independent double wishbone; 5-way preload adjustment, 7.3-in travel
Tires / Front	AT25x8-12 NHS	AT25x8-12 NHS	AT25x8-12 NHS
Tires / Rear	AT25x10-12 NHS	AT25x10-12 NHS	AT25x10-12 NHS

<b>Dimensions</b>			
Bed Capacity	400 lb	400 lb	400 lb
Fuel Capacity	7.9 gal	7.9 gal	7.9 gal
Ground Clearance	12.1 in	12.1 in	12.1 in
L x W x H	113.6 x 56.6 x 73 in	113.6 x 54.4 x 73 in	113.6" x 54.4" x 73.0"
Towing Capacity	1212 lb	1212 lb	1212 lb
Turning Radius	153.5 in	153.5 in	153.5 in
Wet Weight	1199 lb	1190 lb	1105 lb
Wheelbase	75.2 in	75.2 in	75.2 in

<b>Other</b>			
Instrumentation	Digital LCD Multifunction display; speedo, odo, dual trip, hour, clock, fuel, and gear position	Digital LCD Multifunction display; speedo, odo, dual trip, hour, clock, fuel, and gear position	Fuel sight gauge, 4WD Indicator lights (optional digital speedo/fuel)

Lighting	Dual 30W Krypton multireflector headlights & dual 21/5W brakelight	Dual 30W Krypton multi-reflector headlights & dual 21/5W brakelight	Dual 30W Krypton multi-reflector headlights & dual 21/5W brake light
Warranty	6 Month (Limited Factory Warranty)	6 Month (Limited Factory Warranty)	6 Month (Limited Factory Warranty)

\*Prices and specifications subject to change without notice. Please read your Owner's Manual and all labels before operation.

©2010 Yamaha Motor Corporation, U.S.A.